



UltraCare™

Heavy-Duty Sealer & Coating Stripper

DESCRIPTION

UltraCare Heavy-Duty Sealer & Coating Stripper is a professional-strength formulation that helps to remove tough coatings, lacquers, varnishes, sealers, paints and epoxy grout haze from surfaces. This product effectively dissolves heavy wax, and helps to remove deep-set stains and heavy grease buildup. *UltraCare* Heavy-Duty Sealer & Coating Stripper is water-based, pleasantly scented, nonflammable and easy to use.

FEATURES AND BENEFITS

- Nonflammable and formulated to stay on the surface longer for easier stain removal
- Helps to dissolve heavy grease buildup
- Removes most sealers, epoxy grout haze, urethane coatings, synthetic finishes, adhesives and paints
- Easy to use and rinses with water

WHERE TO USE

Most natural stone, grout, ceramic, porcelain, terra cotta, Saltillo, quarry tiles, cement terrazzo, concrete, pavers and masonry surfaces

LIMITATIONS

- Ensure that the product does not come in contact with any non-recommended surface.
- Do not mix with other chemicals.

Consult MAPEI's Technical Services Department for application recommendations regarding surfaces and conditions not listed.

PRODUCT APPLICATION

Choose all appropriate safety equipment before use. Refer to the Safety Data Sheet for details.

Always test first in several inconspicuous areas to confirm desired results.

1. Avoid skin and eye contact by wearing chemical-resistant gloves and protective lenses.
2. Shake container well before using.
3. Working in a small, manageable area of 15 sq. ft. (1,39 m²), liberally apply an even coat over the required area with a paintbrush, roller, mop or sponge.
4. Do not dilute.
5. Allow product to stand on top of surface for at least 1 hour without drying, or until the coating or sealer softens. If the product dries, mist the surface with water to keep it wet.
6. Agitate with scrubpads or with a brush or scrub machine.
7. Remove the residue with a wet vac or with clean, absorbent, white cotton towels.
8. Rinse the surface thoroughly with clean water, removing the water with a wet vac or with clean, absorbent, white cotton towels. Do not track cleaner residue into adjacent areas.
9. Repeat the process as necessary.
10. Surface will be ready for light traffic in as soon as 1 hour.
11. Allow at least 48 hours of drying time before applying *UltraCare* sealers and finishes.



Close container tightly after each use. Store in original container only. Store between the temperatures of 35°F to 90°F (2°C to 32°C). Do not allow to freeze.

For ongoing maintenance instructions, refer to the *UltraCare* Maintenance Guide.

Shelf Life and Application Properties

Shelf life	Up to 5 years when stored in the original sealed container
Appearance	Thick liquid
Odor	Citrus
Physical state	Liquid
VOCs	245 g per L

Packaging

Size
Bottle: 1 U.S. qt. (946 mL)
Jug: 1 U.S. gal. (3,79 L)

Approximate Coverage*

Size	Coverage
1 U.S. qt. (946 mL)	15 to 50 sq. ft. (1,39 to 4,65 m ²)
1 U.S. gal. (3,79 L)	60 to 200 sq. ft. (5,57 to 18,6 m ²)

* Coverage will vary depending on density, porosity, texture, surface absorption, time that the solution is left on the surface, application method, severity of the problem and dilution used.

Refer to the SDS for specific data related to health and safety as well as product handling.

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in effect at the time of the MAPEI product installation. For the most up-to-date TDS and warranty information, please visit our website at

www.mapei.com. **ANY ALTERATIONS TO THE WORDING OR REQUIREMENTS CONTAINED IN OR DERIVED FROM THIS TDS SHALL VOID ALL RELATED MAPEI WARRANTIES.**

Before using, the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability. **ANY CLAIM SHALL BE DEEMED WAIVED UNLESS MADE IN WRITING TO US WITHIN FIFTEEN (15) DAYS FROM DATE IT WAS, OR REASONABLY SHOULD HAVE BEEN, DISCOVERED.**

We proudly support the following industry organizations:



MAPEI Headquarters of the Americas
1144 East Newport Center Drive
Deerfield Beach, Florida 33442
1-888-US-MAPEI (1-888-876-2734) /
(954) 246-8888

Technical Services
1-800-992-6273 (U.S. and Puerto Rico)
1-800-361-9309 (Canada)
Customer Service
1-800-42-MAPEI (1-800-426-2734)

Services in Mexico
0-1-800-MX-MAPEI (0-1-800-696-2734)
Edition Date: March 8, 2017
PR: 6645 MKT: 16-2432

For the most current **BEST-BACKED™** product data and warranty information, visit www.mapei.com.

All Rights Reserved. Printed in the USA. © 2017 MAPEI Corporation.