



TILE + STONE
SOURCE

FALAKRO WHITE
HD PORCELAIN TILE



18x36 FALAKRO WHITE MATTE

FALAKRO WHITE
POLISHED + MATTE
HD PORCELAIN TILE



12x24 FALAKRO WHITE POLISHED + MATTE
HD PORCELAIN TILE

FALAKRO WHITE
POLISHED + MATTE
HD PORCELAIN TILE



18x36 FALAKRO WHITE
HD PORCELAIN TILE
330-102 (POLISHED) 330-104 (MATTE)



12x24 FALAKRO WHITE
HD PORCELAIN TILE
330-101 (POLISHED) 330-103 (MATTE)

Packaging Information

DESCRIPTION	ITEM CODE		LBS/BOX	PCS/BOX	SQFT/BOX	PCS/SKID	SQFT/SKID
FALAKRO WHITE 12x24	330-101	330-103	72	8	16	320	640
FALAKRO WHITE 18x36	330-102	330-104	64.2	3	13.5	87	391.5

General Specifications - Polished

DESCRIPTION	METHOD	UNIT	12"x24"	18"x36"
ACTUAL SIZE	ISO 10545-2	mm - in	297 x 600 mm 11.8 x 23.6 in	450 x 900 mm 17.7 x 35.4 in
THICKNESS	ISO 10545-2	mm - in	9.6 mm 0.38 in	9.8 mm 0.39 in
WATER ABSORPTION	ISO 10545-3	(%)	≤ 0.1	≤ 0.1
ABRASION RESISTANCE	ISO 10545-4	(PEI)	Class 3	Class 3
SCRATCH HARDNESS	EN 15771	(Mohs)	5	5
BREAKING STRENGTH	ISO 10545-4	(N)	≥ 1300	≥ 1300
CHEMICAL RESISTANCE	ISO 10545-13	(GL)	Class GLA	Class GLA
FROST RESISTANCE	ISO 10545-12		Fully Resistant	Fully Resistant
STATIC COF (WET)		(μ)	≥ 0.60	≥ 0.60
STATIC COF (DRY)		(μ)	≥ 0.70	≥ 0.70
SHADE VARIATION			V3	V3

General Specifications - Matte

DESCRIPTION	METHOD	UNIT	12"x24"	18"x36"
ACTUAL SIZE	ISO 10545-2	mm - in	297 x 600 mm 11.8 x 23.6 in	450 x 900 mm 17.7 x 35.4 in
THICKNESS	ISO 10545-2	mm - in	9.6 mm 0.38 in	9.8 mm 0.39 in
WATER ABSORPTION	ISO 10545-3	(%)	≤ 0.1	≤ 0.1
ABRASION RESISTANCE	ISO 10545-4	(PEI)	Class 4	Class 4
SCRATCH HARDNESS	EN 15771	(Mohs)	8	8
BREAKING STRENGTH	ISO 10545-4	(N)	≥ 1300	≥ 1300
CHEMICAL RESISTANCE	ISO 10545-13	(GL)	Class GLA	Class GLA
FROST RESISTANCE	ISO 10545-12		Fully Resistant	Fully Resistant
STATIC COF (WET)		(μ)	≥ 0.70	≥ 0.70
STATIC COF (DRY)		(μ)	≥ 0.70	≥ 0.70
SHADE VARIATION			V3	V3



Tile + Stone Source

#105, 6204 6A St SE
Calgary, AB T2H 2B7
403.252.8868

15304 111 Ave NW
Edmonton, AB T5M 4C8
780.756.8453

www.tilestonesource.com