



TILE + STONE
SOURCE

SNOW SHADOW
HD PORCELAIN TILE



24x24 SNOW SHADOW POLISHED

SNOW SHADOW
POLISHED + MATTE
HD PORCELAIN TILE



12x24 SNOW SHADOW POLISHED + MATTE
HD PORCELAIN TILE

SNOW SHADOW
POLISHED + MATTE
HD PORCELAIN TILE



24x24 SNOW SHADOW
HD PORCELAIN TILE
329-102 (POLISHED) 329-104 (MATTE)



12x24 SNOW SHADOW
HD PORCELAIN TILE
329-101 (POLISHED) 329-103 (MATTE)

Packaging Information

DESCRIPTION	ITEM CODE		LBS/BOX	PCS/BOX	SQFT/BOX	PCS/SKID	SQFT/SKID
SNOW SHADOW 12x24	329-101	329-103	72	8	16	320	640
SNOW SHADOW 24x24	329-102	329-104	73.2	4	16	144	576

General Specifications - Polished

DESCRIPTION	METHOD	UNIT	12"x24"	24"x24"
ACTUAL SIZE	ISO 10545-2	mm - in	297 x 600 mm 11.8 x 23.6 in	600 x 600 mm 23.6 x 23.6 in
THICKNESS	ISO 10545-2	mm - in	9.6 mm 0.38 in	9.6 mm 0.38 in
WATER ABSORPTION	ISO 10545-3	(%)	≤ 0.1	≤ 0.1
ABRASION RESISTANCE	ISO 10545-4	(PEI)	Class 3	Class 3
SCRATCH HARDNESS	EN 15771	(Mohs)	5	5
BREAKING STRENGTH	ISO 10545-4	(N)	≥ 1300	≥ 1300
CHEMICAL RESISTANCE	ISO 10545-13	(GL)	Class GLA	Class GLA
FROST RESISTANCE	ISO 10545-12		Fully Resistant	Fully Resistant
STATIC COF (WET)		(μ)	≥ 0.60	≥ 0.60
STATIC COF (DRY)		(μ)	≥ 0.70	≥ 0.70
SHADE VARIATION			V3	V3
CONTENT OF RECYCLED MATERIAL			0.02	0.02

General Specifications - Matte

DESCRIPTION	METHOD	UNIT	12"x24"	24"x24"
ACTUAL SIZE	ISO 10545-2	mm - in	297 x 600 mm 11.8 x 23.6 in	600 x 600 mm 23.6 x 23.6 in
THICKNESS	ISO 10545-2	mm - in	10 mm 0.39 in	10 mm 0.39 in
WATER ABSORPTION	ISO 10545-3	(%)	≤ 0.1	≤ 0.1
ABRASION RESISTANCE	ISO 10545-4	(PEI)	Class 4	Class 4
SCRATCH HARDNESS	EN 15771	(Mohs)	8	8
BREAKING STRENGTH	ISO 10545-4	(N)	≥ 1300	≥ 1300
CHEMICAL RESISTANCE	ISO 10545-13	(GL)	Class GLA	Class GLA
FROST RESISTANCE	ISO 10545-12		Fully Resistant	Fully Resistant
STATIC COF (WET)		(μ)	≥ 0.70	≥ 0.70
STATIC COF (DRY)		(μ)	≥ 0.70	≥ 0.70
SHADE VARIATION			V3	V3
CONTENT OF RECYCLED MATERIAL			0.02	0.02





TILE + STONE
SOURCE

Tile + Stone Source
#105, 6204 6A St SE
Calgary, AB T2H 2B7
403.252.8868

15304 111 Ave NW
Edmonton, AB T5M 4C8
780.756.8453

tilestonesource.com